

NSAFE

ENGINEERING INC.

GuideWalk™

Rooftop Ladder Access
Innovation, Engineering and
Compliance for worker safety

GuideWalk offers worker protection when accessing flat roofs from ladders

- Free Standing
- Entirely Non-Penetrating
- Easy to install
- Hot-dipped Galvanized
- Optional powder coating
- Used on roofs with or without a parapet

GuideWalk™

FEATURES

- Meets and exceeds OSHA Regulations and Standards for Guard Railings
- GuideWalk is completely independent of ladder
- Entirely non-penetrating design-eliminates all potential for roof damage
- Elevated walking surface-eliminates trip and weather hazards
- Comes standard with all pipes and components hot dipped galvanized
- Optional powder coated-any colour
- Optional self-closing gate
- Easy Installation on any type of flat roof surface up to 15 degree grade
- Applicable for ladders with cages and/or ladders with fall protection
- Assembled on roofs with any size parapet and roofs without parapets



SPECIFICATIONS

- GuideWalk extends 6 ft (1.8m) onto the roof
- Railings are 42 in (1.1m) high including Mid Rail
- Assembles with a single Allen wrench
- Utilizes standard sized pavers-can be supplied or purchased separately (11 pavers 18"x18"-460mm x460mm)
- Custom lengths and heights can be provided.

Distributed By:

Optional Self-Closing Gate